

SLIDE WAY OIL

68,220

(Code: 7080, 7081)

DEFINITION

SLIDE WAY OIL is recommended for machine equipment where a slideway motion is at hand. It is also used for circulating lubrication of bearings and gears. **SlideWay** is fortified with tackifiers to reduce sling off and improve performance.

PROPERTIES

Grade ISO	<u>68</u>	<u>220</u>
Viscosity @ 40 C cSt	66	211
Viscosity @ 100 C cst	7.7	16.5
Flash Point C	204	216
Pour Point C	-15	-11

APPLICATIONS

SLIDE WAY OIL will adhere to the working surfaces under high load and temperature and resist wash out from water soluble cutting fluids.

PACKAGE SIZE

205 Litre, 60 Litre, 20 Litre.

- Materials Safety Data Sheet for this product can be obtained by visiting Ausfield Lubricants Website www.ausfieldlubricants.com.au
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

AUSFIELD LUBRICANTS
Factory 1/36 Mickle St, Dandenong
South VIC 3175
PHONE: (03) 9768 3532
FAX: (03) 9768 3534
EMAIL:
ausfieldlubricants@bigpond.com